

NOBLELIFT

Workstation ANB

Available for the ANB510

Key Features



■ 4 in 1

The workstation is equipped with an array of automatic functions that ensure effortless maintenance of the robot. From charging to refilling clean water, draining waste water, and filling detergent, this station has got covered. Discover hassle-free maintenance like never before with our innovative working station.

■ Friendly user interface

The clear and concise human-machine interface enables people to understand the working mode and status of the working station without special training, which increases efficiency and reduces training costs.

■ High level of safety

This charger has been certified by both CE and UL, demonstrating that it meets rigorous safety standards. With dual signal loss feature, the working station automatically shuts down if the robot becomes detached, providing an additional layer of safety. The station also incorporates multiple protective features, including over-temperature, short-circuit, and over-voltage protections, further bolstering its safety performance. These benefits make our clean robot workstation a trustworthy and secure solution for your needs.



ANB510

Specifications

| | |
|------------------------|------------------------------------|
| Dimensions (Main body) | 460*270*860 mm 18.1*10.6*33.9 in |
| Weight | 45 Kg 99 lbs |
| Input Voltage | 100-240 V a.c |
| Max.Power | 1000 W 1.34 hp |
| Output Voltage | 24 V |
| Operating Temperature | 0°C ~45°C |

NOBLELIFT North America

2475 S Wolf Rd, Des Plaines, IL 60018 | www.NobleliftNA.com | Sales@NobleliftNA.com | 847-595-7100

NOBLELIFT

Charging Station ANS

Key Features



■ Hassle-free maintenance with charging station

The charging station has the feature of automatically charging for the cleaning robots. When the battery is low, the robot has the ability to automatically return to the charging station to recharge itself, and once the charging is complete, it can automatically resume its previous task. Discover hassle-free maintenance like never before with our innovative working station.

■ Compact design

The charging station saves space, offers flexibility, and ensures efficient cleaning. Its small footprint allows easy placement in any location, and optimal utilization of available floor area. The design provides convenience and enhances overall cleaning efficiency.

■ High level of safety

This charger has been certified by both CE and UL, demonstrating that it meets rigorous safety standards. With dual signal loss feature, the working station automatically shuts down if the robot becomes detached, providing an additional layer of safety. The station also incorporates multiple protective features, including over-temperature, short-circuit, and over-voltage protections, further bolstering its safety performance. These benefits make our clean robot workstation a trustworthy and secure solution for your needs.

Available for the ANB510 and ANS720



ANB510



ANS720



Specifications

| | |
|------------------------|----------------------------------|
| Dimensions (Main body) | 420*225*620 mm 6.5*8.9*24.4 in |
| Weight | 27 Kg 60 lbs |
| Input Voltage | 100-240 V a.c |
| Max.Power | 1000 W 1.34 hp |
| Output Voltage | 24 VDC |
| Operating Temperature | 0°C ~45°C |

NOBLELIFT North America

2475 S Wolf Rd, Des Plaines, IL 60018 | www.NobleliftNA.com | Sales@NobleliftNA.com | 847-595-7100